



# EpiMax MATERIAL SAFETY DATA SHEET

Product Name **EPIMAX 2150**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier Name** EPIMAX TECHNOLOGIES PTY LTD  
**Address** 4/3 Moorebank Avenue, Moorebank, NSW, AUSTRALIA, 2170  
**Telephone** 1300 721 522  
**Fax** (02) 9904 3207  
**Emergency** 1300 721 522  
**Synonym(s)** 2150 • 9215020 - PRODUCT CODE • WATER BASED CONCRETE DENSIFIER  
**Use(s)** SINGLE PACK CONCRETE DENSIFIER AND SEALER  
**SDS Date** 09/03/12

## 2. HAZARDS IDENTIFICATION

### RISK PHRASES

R20/22 Harmful by inhalation and if swallowed  
R36/38 Irritating to eyes and skin.  
R41 Risk of serious damage to eyes  
R43 May cause sensitisation by skin contact

### SAFETY PHRASES

S2 Keep out of reach of children  
S24/25 Avoid contact with skin And eyes  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice  
S28 After contact with skin, wash immediately with plenty of water  
S37/39 Wear suitable gloves and eye/ face protection

<b>UN No.</b>	None Allocated	<b>DG CLASS</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Packing Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated		

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS NO.	Content
SODIUM SILICATE	Na <sub>2</sub> O <sub>3</sub> Si	1344-09-8	10% - 30%
POTASSIUM METHYLSILICONATE	NOT AVAILABLE	31795-24-1	< 10%
INGREDIENTS DETERMINED TO BE NON HAZARDOUS, OR BELOW BUT OFF CONCENTRATIONS			TO 100%

Product Name: **EPIMAX 2150**

#### 4. FIRST AID MEASURES

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Airline respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>Special Treatment</b>	Treat symptomatically.

#### 5. FIRE FIGHTING MEASURES

<b>Special Hazards</b>	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
<b>Advice for firefighters</b>	Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing Media</b>	Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways.
<b>Hazchem Code</b>	None Allocated

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Spillage</b>	Contact emergency services where appropriate. Use personal protective equipment. Clear area of all unprotected personnel. Ventilate area where possible. Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all ignition sources.
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### 7. STORAGE AND HANDLING

<b>Storage</b>	Store tightly sealed in a cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems. Store as a Class C1 Combustible Liquid (AS1940).
<b>Precautions for safe handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

Product Name: **EPIMAX 2150**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTIONS

<b>Exposure Stds</b>	No exposure standard(s) allocated.
<b>Biological Limits</b>	No biological limit allocated.
<b>Engineering Controls</b>	Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.
<b>PPE</b>	Wear splash-proof goggles, nitrile or viton (R) gloves, coveralls and a Type A (Organic vapour) respirator. If sanding dry product, wear: a Class P1 (Particulate) respirator. If spraying, with prolonged use, or if in confined areas, wear: impervious coveralls and an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	MILKY LIQUID	<b>Solubility (water)</b>	SOLUBLE
<b>Odour</b>	MILD	<b>Specific Gravity</b>	1.15
<b>pH</b>	NOT AVAILABLE	<b>% Volatiles</b>	70% - 80%
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	NOT FLAMMABLE
<b>Vapour Density</b>	NOT AVAILABLE	<b>Flash Point</b>	NOT AVAILABLE
<b>Boiling Point</b>	100°C	<b>Upper Explosion Limit</b>	NOT AVAILABLE
<b>Melting Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	NOT AVAILABLE
<b>Evaporation Rate</b>	NOT AVAILABLE	<b>Decomposition Temperature</b>	NOT AVAILABLE
<b>Autoignition Rate</b>	NOT AVAILABLE	<b>Viscosity</b>	NOT AVAILABLE
<b>Partition Coefficient</b>	NOT AVAILABLE		

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under recommended conditions of storage.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources.
<b>Material to avoid</b>	Incompatible with oxidising agents (eg. hypochlorites), acids (eg. nitric acid), alkalis (eg. hydroxides), heat and ignition sources.
<b>Hazardous Decomposition Products</b>	May evolve toxic gases (carbon oxides, phenols, hydrocarbons) when heated to decomposition.
<b>Hazardous Reactions</b>	Hazardous polymerization is not expected to occur.

## 11. TOXICOLOGICAL INFORMATION

<b>Health hazard summary</b>	Irritant - low to moderate toxicity. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and inhalation. May cause sensitisation by skin contact. The cured product is considered non toxic.
<b>Eye</b>	Irritant. Will cause burning, stinging, tearing, and redness. Can cause severe irritation if not treated.
<b>Inhalation</b>	Irritant. Over exposure whilst curing may result in irritation of the nose and throat, coughing,

**Product Name: EPIMAX 2150**

possible sensitisation with asthma-like symptoms and pulmonary oedema at high levels.

**Skin** Irritant. Contact may result in irritation, redness, rash and dermatitis. May cause sensitisation by skin contact.

**Ingestion** Low to moderate toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, abdominal pain and diarrhoea.

**Toxicity Data** There is no toxicological information available for this product.

**12. ECOLOGICAL INFORMATION**

**Other adverse effects** Limited ecotoxicity data was available for this product at the time this report was prepared. Ensure appropriate measures are taken to prevent this product from entering the environment.

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal** Neutralise with dilute hydrochloric acid and flush the affected area with water. Ensure protective equipment is worn when mixing. Do not seal containers/tins until reaction is complete. Contact the manufacturer for additional information. Prevent contamination of drains or waterways as environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

**14. TRANSPORT INFORMATION****NOT CLASSIFIED AS A DANGEROUS GOOD THE CRITERIA OF THE ADG CODE**

<b>Shipping Name</b>	NONE ALLOCATED				
<b>UN No.</b>	NONE ALLOCATED	<b>DG CLASS</b>	NONE ALLOCATED	<b>Subsidiary Risk(s)</b>	NONE ALLOCATED
<b>Packing Group</b>	NONE ALLOCATED	<b>Hazchem Code</b>	NONE ALLOCATED	<b>GTEPG</b>	NONE ALLOCATED

**15. REGULATORY INFORMATION**

**Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

**AICS** All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

**16. OTHER INFORMATION**

**Additional information** WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate) respirator is recommended if dust is generated.  
EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to

**Product Name:**

**EPIMAX 2150**

enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken.

Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

ABBREVIATIONS:

ACGIH - American Conference of Industrial Hygienists.

ADG - Australian Dangerous Goods.

BEI - Biological Exposure Indice(s).

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EC No - European Community Number.

HSNO - Hazardous Substances and New Organisms.

IARC - International Agency for Research on Cancer.

mg/m<sup>3</sup> - Milligrams per Cubic Metre.

NOS - Not Otherwise Specified.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

STEL - Short Term Exposure Limit.

SWA - Safe Work Australia.

TWA - Time Weighted Average.