

ELASTOCOL STICK

TECHNICAL DATA SHEET
110712SCAN2E
(supersedes 100326SCAN1E)

DESCRIPTION

ELASTOCOL STICK is a primer designed to enhance the adhesion of self-adhesive membranes on porous surfaces such as "DENS GLASS GOLD" and "DENS DECK" at temperatures above -10°C. It is composed of SBS synthetic rubbers, adhesive enhancing resins and volatile solvents. It is also suitable to prime non-porous surfaces such as concrete, fibre cement, metal, and wood.

APPLICATION

ELASTOCOL STICK can be applied with a brush, a roll or a spray can. It must be thoroughly dry before applying the waterproofing membrane. **ELASTOCOL STICK** must be shaken well before use.

WARNING: DO NOT ACCELERATE DRYING OF ELASTOCOL STICK BY HEATING IT WITH A TORCH.

Average coverage, porous surfaces: 0.3 to 0.5 L/m²,
non-porous surfaces: 0.1 to 0.25 L/m².

PROPERTIES

SOPRAMASTIC ALU meets the requirements of CAN/CGSB-37.5-M89 and ASTM D4586 standards.

| Properties | Standards | ELASTOCOL STICK |
|--------------------------------|-----------|------------------|
| Specific Gravity at 20 °C | - | 0.79 kg/L |
| Colour | - | Red |
| Solids by Weight | - | 24 % |
| Viscosity, Brookfield at 25 °C | - | 200 cP |
| Flash Point | ASTM D93 | -30 °C (0 °F) |
| Drying time | - | 15 to 60 minutes |

(All values are nominal)

PACKAGING

3.78 L, 19 L pails and 350 g spray cans.

Shelf life: Up to 2 years in original sealed containers, in cool and ventilated area.

CLEANING

Tools can be cleaned with petroleum solvents such as mineral spirits, varsol, xylene, etc.

PRECAUTIONS

ELASTOCOL STICK IS A HIGHLY FLAMMABLE PRODUCT.

Store away from direct sunlight and open flame. Keep ignition sources away during application and until solvent has evaporated. Harmful if inhaled, swallowed or when in contact with the skin. In closed area, ventilate carefully using mechanical means if necessary. Do not pour residues in drains.

CONSULT THE MATERIAL SAFETY DATA SHEET PRIOR TO USE.

