



HPG-130 Cleaner

Polyurethane Injection Pump Cleaner

Technical information

HPG-130 Cleaner is a premium grade, pump maintenance solution for the cleaning and lubrication of polyurethane pumps and associated equipment. When used as a part of a regular start-up and shut-down procedure HPG-130 Cleaner prolongs the life of the pump, its seals and all moving parts by preventing the build up of hardened resin in and around seals.

Advantages

- Non-toxic
- Non-flammable
- Lubricates moving parts within the pump
- Removes contamination from pumps, seals and lines
- Will not damage seals or lines

TECHNICAL DATA

- Colour - Clear
- Viscosity - <50 cps
- Flash point. - 185°C
- Density - 1.25kg/litre

Packaging

- 20lt pail

Storage

- Store between 10° and 40C°
- Keep containers closed when not in use
- Stir well before use
- Shelf life -12 months in un-opened containers

Application

Before injecting HPG-130

1. Run the pump dry to remove as much of the old cleaner, storage solution or liquid as possible.
2. Fully prime the pump and lines with fresh HPG-130 Cleaner
3. Close off hand piece and run in short bursts to force the cleaner in and around the pump seals. Be careful NOT to over pressurise the unit.
4. Release the pressure and cycle a small amount into a collection pail. Keep pumping the solution until it becomes clear and free of any discoloration or solid matter. Responsibly discard any waste product.
5. Run the pump and lines dry before priming the pump with the HPG-130 polyurethane injection resin.

After injecting HPG-130

1. Repeat steps 1 to 4 as above

Safety

Avoid contact with skin and eyes
Wear safety glasses, gloves and overalls
Avoid inhaling fumes
Read MSDS before use.

Warranty Information - This limited warranty is limited to the replacement of the materials which are defective. Allduro makes no other warranty, expressed or implied, and makes no warranty of merchantability or fitness for a particular purpose. This limited warranty does not include any transportation charges or costs of installation or any liability for direct, indirect, consequential, or punitive damages or delay, whether or not the undersigned has been advised of such claims. THE FOREGOING LIMITED WARRANTY IS THE SOLE WARRANTY FOR THE PRODUCT. THERE ARE NO OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THE WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Allduro 14 Vulcan Road Canning Vale WA 6155 T. 08 9455 1658 • www.allduro.com

The information provided in this technical bulletin is as correct in detail as possible and is intended to give a fair description of the product and its capabilities. In practice, the substrate and environmental conditions vary widely, making it essential for the user to determine the products suitability for a particular application and that the product is not used beyond its physical limitations. The product is guaranteed providing that it is applied in accordance with the manufacturer's instructions as stated in this data sheet and any relevant Standard or Code and provided that the building and installation is structurally sound. Allduro terms and conditions of sale apply.

ALLDURO